8-Port Enterprise KVM Switch

SPECIFICATION AND PRODUCT FEATURES

Model	SP218D
Computer Connection	Direct: 8
	After Cascade: 120
LED Indicator	Red: Live
	Blue: Selected
Interface	1 x Local Monitor VGA port (HDDB-15)
	1 x Local Keyboard/Mouse USB port (mini din 6-pin)
	1 x Daisy Chain port
Computer Connector	8 x PC Ports (HDDB-15)
Methods of Control	Push button, Hot-key, OSD
Auto Scan Interval	5 ~ 99 seconds
VGA Resolution	2048 x 1560
Cable Type	3-in-1 (Monitor, Mouse, Keyboard) HDDB-15 connector
Operating Temp	0 ~ 50 °C
Storage Temp	-20 ~ 60 °C
Humidity	0 ~ 95%, Non-Condensing
Power	DC Power Adapter: 12 VDC, 1A
	1.825 kg

The product specifications are subject to change without prior notice.

ORDERING INFORMATION

Model	Description
SP218D	8-Port Enterprise KVM Switch
C200K-1	3-in-1 PS/2 KVM cable, 1.8 Meters(W/ C200K/C USB/PS2 converter)
C200K-3	3-in-1 PS/2 KVM cable, 3 Meters(W/ C200K/C USB/PS2 converter)
C200K-5	3-in-1 PS/2 KVM cable, 5 Meters(W/ C200K/C USB/PS2 converter)
C200K-C	PS/2 - USB Converter
C200K-D	Daisy Chain Cable
C200L-1	3-in-1 USB KVM cable, 1.8 Meters
C200L-3	3-in-1 USB KVM cable, 3 Meters
C200L-5	3-in-1 USB KVM cable, 5 Meters



SP218D KVM Switch

- 2 Bank LED
- Over Jack
- 4 Local Console Port for USB/VGA
- 5 Daisy-Chain Connector
- 6 Remote connector for USB/PS2 PC
- IP Card slot(optional for IP Card)

COMPANION PRODUCTS
Consider the following Micronet products as a factor in your network planning.
Ethernet Switch
Industrial Ethernet
IP Surveillance
Wireless LAN
VDSL ADSL and Broadband
IP Telephony
KVM Switch
Network Appliance
Structured Cabling System

Distributor:

Micronet Communications Inc.

E-mail: sales@micronet.com.tw; support@micronet.com.tw Web: www.micronet.com.tw